

5RS095



All-in-one commercial downlight range




KEY FEATURES

- 3CCT Switchable (3000K/4000K/6000K)
- Interchangeable reflector options
- Loop in & loop out driver
- Self-made Dali driver available
- High efficiency 105lm/w
- Die-casting aluminum body

 Dimmable	 CRI 80/90	 AC 220-240V	 PF >0.9	 Low glare
 DALI / 0-10v Dimmable	 IP54 Front	 60°/90°	 Emergency	 5 YEARS

Dimensions



	5RS095/129	5RS084/130	5RS121/122	5RS123/124
Total Power:	8W/10W	15W/18W	20W/25W	30W/35W
Size(AxBxC):	110x55x88mm	150x68x123mm	172x69x148mm	228x88x198mm
Cutout:	Φ 90-95mm	Φ 125-135mm	Φ 150-165mm	Φ 200-210mm
lm/W:	≥105 lm/W	≥105 lm/W	≥105 lm/W	≥105 lm/W
CCT Changeable:	3000K 4000K 6000K	3000K 4000K 6000K	3000K 4000K 6000K	3000K 4000K 6000K

Interchangeable reflectors



60° Diamond



60° Specular



90° Diamond



90° Specular

Self-made driver



Dali/0-10v



TRAIC